

KNX

BACnet

MQTT

Modbus

OPC  
(DA/UA)

SNMP

Fidelio/Opera | Protel | Infor  
RMS Cloud | CharPMS  
VingCard Web | Kaba | Salto


DALI EnOcean  
M-Bus DMX

Proprietary solutions

# All-in-one

**Building management software for  
medium-sized and enterprise building  
automation projects**

**Building automation systems**



## Building Automation Systems (BAS)

aim at improving control and management of mechanical and electrical systems in buildings

## Modern BAS are distributed systems


where embedded devices are connected via computer networks to exchange information and data

Core application areas are lighting/shading and heating, ventilation, and air conditioning (HVAC)

Today other application domains are integrated too

- Security systems (access control, CCTV, security alarm systems, ...)
- Safety systems (fire alarm systems, water leakage detection, CO2 monitoring, ...)
- Smart metering and energy management systems
- ...


# Building automation systems



Building Management Systems (BMS) are located at the management level to provide management tasks

- Visualization, trending, remote access, alarm management, and other maintenance tasks
- Integration of different subsystems into “all-in-one” solution

# Why building automation?





# Increase user comfort





## Increase accessibility and usability of the building

Increase user comfort

Safety & security

Prestige

## Decrease the operational costs

Decrease costs of maintenance

Decrease costs of used resources (energy efficiency)

## Contribute to environmental protection

Decrease energy demand

Nearly Zero Energy Buildings

Reduce carbon footprint

### Additional social benefit

“My house, my car,  
my building automation system”

### Advanced applications


- Control your smart home/building from your smartphone
- Personalized visualization tailored to your desires

### Use latest technologies


- Impress your guests with your smart home/building



# Decrease operational costs



# Decrease operational costs of maintenance



# Decreasing energy costs

## Increase accessibility and usability of the building

Increase user comfort

Safety & security

Prestige

## Decrease the operational costs

Decrease costs of maintenance

Decrease costs of used resources (energy efficiency)

## Contribute to environmental protection

Decrease energy demand

Nearly Zero Energy Buildings

Reduce carbon footprint

### A major part of the operation costs are energy costs

- Electricity
- Heating
- Water
- ...

### Buildings must use the available resources in an efficient way in order to decrease costs

- Energy management
- Smart metering
- Smart building
- Smart city

## Increase accessibility and usability of the building

Increase user comfort

Safety & security

Prestige

## Decrease the operational costs

Decrease costs of maintenance

Decrease costs of used resources (energy efficiency)

## Contribute to environmental protection

Decrease energy demand

Nearly Zero Energy Buildings

Reduce carbon footprint



### Today energy-efficient buildings are a must!

- Regulated by law!
- 2002/91/EU, 2010/31/EU: Energy performance of buildings directive
- EN-15232: Energy performance of buildings: Impact of building automation, controls, and building management
- Other directives and national regulations exist too

### Modern buildings must be sustainable and energy-efficient

- Decrease energy demand
- Decrease carbon footprint
- Use renewable energy resources
- Nearly Zero Energy Building (NZEB)
- Nearly Zero Emission Building

### EN 15232: Impact of building automation, controls, and building management

Defines different classes for energy performance of building

- A** Energy-efficient BAS with BMS
- B** Advanced BAS with special BMS functions
- C** Standard BAS
- D** Non efficient BAS

Class A and B are  
not possible without  
BAS and BMS!

Increase in the energy efficiency of buildings has two advantages

- Decrease the energy costs and thus the operational costs
- Contributes to environmental protection

How can the energy efficiency of building be improved?

$$C = \frac{D}{\eta}$$

*C ... Consumption*  
*D ... Demand*  
*η ... Performance*



Acting on the performance of  
equipment and processes

$$C = \frac{D}{\eta \uparrow}$$

*C ... Consumption*

*D ... Demand*

*n ... Performance*

Use the best available technologies

- LED
- Substituting heating devices with poor efficiency
- Use ventilation systems (enthalpy recovery, ...)

### Improving the consumption habits of the users

Use smart metering to show the user the actual consumption (know2reduce)

$$C = \frac{D \downarrow}{\eta}$$

*C ... Consumption*  
*D ... Demand*  
*n ... Performance*

Core application areas

Today other application domains are integrated too

Modern BAS are distributed systems

### Get a high reduction of the demand actively

Depending on

- the real use (presence, schedules, special needs, ...)
- external conditions (temperature, light, humidity, ...)
- bioclimatic criteria (orientation, position of the sun, shadows)

$$C = \frac{D \downarrow \downarrow}{\eta}$$

*C ... Consumption*  
*D ... Demand*  
*η ... Performance*

Use BAS to provide enhanced applications that decrease the demand actively

- Key component is BMS that has global view of all subsystems, devices, and data
- Integration of subsystems and aggregating data and information to provide advanced applications

## Enhanced applications: examples



Integration of hotel  
management systems

Individual room  
temperature control



Smart  
metering



Constant  
light control

Smart grids/  
smart cities




Presence detection  
for HVAC control



Enhanced automatic  
shading control

## Constant light control





In 14 hours (8:00 am to 22:00 pm) only 55% of the installed power used

Presence detection  
as additional input


Decreases energy consumption  
(between 30% and 40% of savings)

Increases user comfort

Required for Class A



## Individual room temperature control




Decreases energy consumption  
(about 30% of savings)


Increases user comfort  
(each habit can set  
its own set point)

Required for Class B

# Presence detection for HVAC control



## NETx Shutter Control - enhanced automatic shading control



3D model of building + neighbor building and surrounding environment

Simulation to calculate optimal position of blinds and their slats

Current weather data + additional inputs are used together with simulated data to control blinds in real time

Decreases energy demand for HVAC system

Increases user comfort

Required for Class B and Class A

Check-in/check-out information can be used to control HVAC system of hotel rooms

- Check-in -> HVAC control is set to "Comfort Mode"
- Check-out -> HVAC control is set to "Eco Mode"

Decreases energy consumption

Increases user comfort

Measurement of the consumption value of the used energy resource is the basis for all energy management applications

- Monitoring for smart metering data (improving the consumption -> know2reduce)
- Analysis and comparison of smart metering data (identifying saving measurements, cost calculation)
- Reacting on smart metering data (e.g. load balancing)

Smart metering  
data is important  
input for  
smart grids

Integration of different technologies, systems, and application domains

Interconnection via Wide Area Network  
(WAN)

Interact with smart grid,  
offer interfaces to the grid

Focus on the total building  
environment (NZEB, ..)

Involve all field which effect  
living, citizens, ...



## Challenges for providing BMS solutions

Enhanced applications can only be provided if all subsystems are connected to BMS


- Integration is of utmost importance


Building automation systems are Heterogeneous


- Many different technologies are used
- Each technology has its characteristics and its own way to represent and process control data
- Integration is a complex task


Sophisticated BMS solution is necessary

BMS is mandatory for Class B and Class A of EN 15232









[www.netxautomation.com](http://www.netxautomation.com)